

Wall mounted unit

FTXP-N9 + RXP-N9



comfora **INVERTER**



Onecta app



Energy saving during standby mode



3-D air flow



Practically inaudible

Discreet wall mounted unit providing high efficiency and comfort

- › Onecta app
- › Practically inaudible
- › Voice control
- › Silver allergen removal and air purifying filter
- › 3-D airflow: air is blown into all corners of a room
- › Ideal for above door installation

- › Bluevolution range: lower environmental impact
- › Seasonal efficiency values up to A++ in cooling and heating
- › Space saving contemporary wall mounted design

FTXP-N9 + RXP-N9



Indoor unit			FTXP		20N9		25N9		35N9	
Dimensions	Unit	HeightxWidthxDepth		mm	286 x770 x225					
Weight	Unit			kg	9.00					
Air filter	Type				Removable / washable					
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/ High	m³/min	4.4 / 5.6 / 7.5 / 9.6		4.4 / 5.8 / 7.5 / 9.9		4.5 / 6.3 / 8.3 / 11.5	
		Heating	Silent operation / Low / Medium / High	m³/min	5.0 / 6.6 / 8.6 / 10.6				5.1 / 7.0 / 9.0 / 11.5	
Sound power level	Cooling			dBA	55				58	
	Heating			dBA	55				58	
Sound pressure level	Cooling	Silent operation/Low/High		dBA	19 / 25 / 39		19 / 26 / 40		20 / 27 / 43	
	Heating	Silent operation/Low/High		dBA	21 / 28 / 39		21 / 28 / 40		21 / 29 / 40	
Control systems	Infrared remote control				ARC480A78					
	Wired remote control				BRC073A1					

Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal) | See separate drawing for electrical data

Outdoor unit				RXP	20N9	25N9	35N9
Dimensions	Unit	HeightxWidthxDepth		mm	556 x740 x343		
Weight	Unit			kg	24		26
Sound power level	Cooling			dBA	-		
Sound pressure level	Cooling	High		dBA	46		48
	Heating	High		dBA	47		48
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10 ~48		
	Heating	Ambient	Min.~Max.	°CWB	-15 ~18		
Refrigerant	Type				R-32		
	GWP				675.0		
	Charge			kg	0.55 /-		0.70 /-
Piping connections	Liquid	OD		mm	6.4		
	Gas	OD		mm	9.5		
	Piping length	OU - IU	Max.	m	20		
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)		
	Level difference IU - OU			Max. m	12		
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50 /220-240		
Current - 50Hz	Maximum fuse amps (MFA)			A	16		

See separate drawing for operation range | See separate drawing for electrical data | Contains fluorinated greenhouse gases

Efficiency data		FTXP + RXP	20N9 + 20N9	25N9 + 25N9	35N9 + 35N9	
Cooling capacity	Nom.	kW	1.3 /2.00 /2.6	1.3 /2.50 /3.0	1.3 /3.50 /4.0	
Heating capacity	Nom./Max.	kW	1.30 /2.50 /3.50	1.30 /3.00 /4.00	1.30 /4.00 /4.80	
Power input	Cooling	Min./Max.	kW	0.31/0.530 /0.72	0.31/0.660 /0.72	0.29 /1.01 /1.30
	Heating	Min.	kW	0.25 /0.520 /0.95	0.25 /0.690 /0.95	0.29 /0.990 /1.29
Space cooling	Energy efficiency class		A++			
	Capacity	Pdesign	kW	2.00	2.50	3.50
	SEER		7.20			
	Annual energy consumption		kWh/a	97	121	170
Space heating (Average climate)	Energy efficiency class		A++			
	Capacity	Pdesign	kW	2.20	2.40	2.80
	SCOP/A		4.65			
	Annual energy consumption		kWh/a	663	728	845

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · België · www.daikin.eu · BE 0412 120 336 · RPR Oostende

Kelvin Sp/f
Tlf 288267-212204



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN24-046

01/2024



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.